

Поршневые компрессоры Danfoss на R134a фреоне

холодопроизводительность при T кипения (T конденсации +55)

модель компрессора	-35	-30	-25	-20	-15	-10	-5	0	5	10	15
TL4F	31	44	61	81	107	137					
TLS7F	66	89	120	160	208	264					
NL6F (LST)	52	77	110	151	200	258					
NL7F (LST)	71	99	136	182	238	303					
NL9F (LST)	80	112	155	208	272	346					
NL11F (LST)	102	144	200	271	356	455					
SC15F	100	155	230	325	439	573					
SC18F	129	194	280	388	518	669	842				
SC21F	185	245	335	455	610	780	990				
TL5G		56	76	103	137	178	227	283	346	416	494
FR7,5G (LST)		66	99	143	197	261	335	420	514	619	
FR8,5G (LST)		84	123	172	231	300	381	474	580	698	
FR10G (LST)		93	137	188	250	323	411	514	636	777	
FR11G (LST)		115	170	233	307	395	501	628	780		
SC10G	43	60	113	183	268	369	486	618	764	925	1100
SC12G	78	115	175	257	360	484	625	785	960	1150	1354
SC15G	91	147	224	322	440	579	737	915	1113	1330	1565
SC18G	117	192	283	394	526	684	870	1087	1337	1624	1950
SC21G	187	245	333	453	606	792	1012	1268	1560	1889	2256